

# PHOTOLUMINESCENT EXIT SIGNS by KENSINGTON EVALUATED AND TESTED TO UL924



90.8924R  
90.8924G



Kensington aluminum exit signs and architectural frames are evaluated and tested to UL924. They conform to life safety, fire and building codes-

- IBC and IFC
- NFPA 1 (UFC) and NFPA 5000
- NFPA 101 (Life Safety Code)

Kensington Exit Signs generally can be used instead of electrical exit signs above the door and at floor level:

- Minimum of 5 ft-candles of fluorescent lighting on the sign face at all times the building is occupied.
- Qualifies for LEED credits, sustainable construction.

Kensington Photoluminescent Exit Signs offer:

- Maximum reliability and effectiveness.
- No electricity, batteries or lamps needed.
- Contains no radioactive or toxic components.
- Durable and attractive aluminum signs and frames.
- Mounting bracket suitable for left, right or top mounting.
- Frame suitable for 1- or 2- side signs.
- Can be used with or without frames and mounting brackets.
- Available in red, green or black background with glow letters.
- Visible and legible from 75 ft.
- Dimensions: 14.25 x 9 inches with frame; 13.74 x 8.5 inches w/o frame.
- Directional chevrons and fasteners included.
- 25 year life.



3048236  
EVALUATED TO THE UL924  
PERFORMANCE STANDARD

